

Harlequin® HydroClear

SEWAGE TREATMENT PLANT

HydroClear HC6 Wastewater Treatment Plant

HydroClear represents significant progress for the domestic wastewater treatment industry.

Contemporary design engineering and analysis software and state-of-the-art manufacturing facilities combine to create this unique product which dominates the sewage treatment plant market with class-leading pollutant removal level of 97%.



Standard Features:

- ◆ Tank body moulded in one piece from durable medium density polyethylene material
- ◆ 110mm inlet and outlet connections
- ◆ Integrated lifting eyes for ease of handling and installation
- ◆ Fully secured 450mm pedestrian duty, flush fitting manhole covers comply with statutory regulations
- ◆ Adjustable turrets allowing for shallower invert levels
- ◆ Above ground air blower housing delivers more reliable and efficient operation, and allows easy access for maintenance
- ◆ Easy access to the bubble diffuser within the tank
- ◆ Virtually silent operation
- ◆ Cost effective installation
- ◆ 24 month service period reduces operating costs
- ◆ HydroClear owners can determine their own de-sludge intervals giving potential cost savings
- ◆ Mechanically reliable with no moving parts or electrics within the tank
- ◆ Certified to EN12566-3

Harlequin® HydroClear

SEWAGE TREATMENT PLANT

HydroClear HC6 Wastewater Treatment Plant

Optional Equipment:

- ◆ Air blower function alarm
- ◆ Pumped outlet
- ◆ 300mm turret extension piece(s) – max. allowable invert level of 2m

Technical Data:

	<i>Efficiency</i>	<i>Effluent</i>
Treatment Efficiency	COD	91.2%
	BOD ₅	96.6%
	NH ₄ -N	85.8%
	SS	94.7%
Nominal hydraulic daily load	1,200Litres / day	
Nominal organic daily load	360g BODs / day	
Inhabitants served	1 - 6	
Desludging interval	12 months *	
Electrical consumption	1.8 kWh / day	
Power requirements	230V 76W 1.0A (start-up current)	
Volumes (at operational height)	Primary settlement – 3000 Litres Aeration chamber – 720 Litres Final settlement – 720Litres	
Overall dimensions	L 3400 W 1250 H 2560 mm	
Standard inlet depth	1090 mm	
Standard outlet depth	1140 mm	
Depth from invert to base	1470 mm	
Depth from base to ground	2560 mm	
Pipe diameter	110 mm	
Net Weight	450 kg	

* de-sludge interval up to 12 months depending on the number of inhabitants

Issued By:

Harlequin Manufacturing Limited
21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB
T: +44 (0)28 9261 1077
W: www.harlequin-mfg.com
E: info@harlequin-mfg.com